

**THE SERIES 20 RUBBER ELASTIC BLACK /ALUMINUM (PROFI SERIES)**

Elastic black rubber wheel.

**swivel castor with central hole 20 80 125 ШТ****Item code:** 20 80 125 ШТ**Link to the product:**[https://www.fregat.com.ua/en/wheels\\_and\\_rollers/wheel/20\\_80\\_125\\_sht-id1405](https://www.fregat.com.ua/en/wheels_and_rollers/wheel/20_80_125_sht-id1405)

For poor quality asphalt and pavement, outdoor uses

For warehouse and loading equipment

**Specification:**

|                                                   |                |
|---------------------------------------------------|----------------|
| <b>Wheel outside diameter:</b>                    | 125 mm         |
| <b>Full height of the product:</b>                | 155 mm         |
| <b>Full height of the product:</b>                | 36 mm          |
| <b>Rolling Surface Material:</b>                  | elastic rubber |
| <b>Rim material:</b>                              | aluminum       |
| <b>Bracket Steel Thickness:</b>                   | 2,5 mm         |
| <b>Steel thickness of the upper rotary panel:</b> | 3 mm           |
| <b>Diameter of central mounting hole:</b>         | 12             |
| <b>Hardness:</b>                                  | 65 Shore A     |
| <b>Working temperature:</b>                       | -20°C — +70°C  |
| <b>Maximum load:</b>                              | 200 kg         |
| <b>Net weight:</b>                                | 1,60 kg        |
| <b>Manufacturer:</b>                              | Torwegge       |

**Description:**

Rubber is connected to the rim of the wheel with vulcanization process, low rolling resistance. The rim of the wheel is cast aluminum alloy on ball bearings.