

**THE SERIES 50 POLYURETHANE / ALUMINIUM**

Yellow polyurethane wheel with aluminum rim and ball bearings.

swivel castor with top plate 50 22 160 ШФ**Item code:** 50 22 160 ШФ**Link to the product:**https://www.fregat.com.ua/en/wheels_and_rollers/wheel/50_22_160_shf-id1502

For high loads

For window productions

For warehouse and loading equipment

Specification:

| | |
|--|---------------|
| Wheel outside diameter: | 160 mm |
| Full height of the product: | 200 mm |
| Full height of the product: | 56 mm |
| Rolling Surface Material: | polyurethane |
| Rim material: | aluminum |
| Bracket Steel Thickness: | 4 mm |
| The thickness of the steel of mounting plate: | 6 mm |
| Outside size of mounting plate: | 135x110 |
| The distance between the mounting holes and their diameter: | 105x080x11 |
| Hardness: | 92 Shore A |
| Working temperature: | -20°C — +80°C |
| Maximum load: | 500 kg |
| Manufacturer: | Fregat |

Description:

The rim of the wheel is made of cast aluminum, which forms an inseparable connection with the rolling surface through a chemical and geometric force. The polyurethane rolling surface has both high payload capacity and good elasticity, durability and low rolling resistance.