FREGAT LLC





49000, Dnipropetrovsk region, Dnipro city, Grushevsky Mikhail, 12, office 2-B Showroom and address for correspondence: пр. Александра Поля, дом 59, г. Днепр, Украина, 49101 E-Mail: info@fregat.com.ua

https://www.fregat.com.ua/



THE SERIES 50 POLYURETHANE / ALUMINIUM

Yellow polyurethane wheel with aluminum rim and ball bearings.

swivel castor with top plate 50 24 160 ШФ

Item code: 50 24 160 ШФ

Link to the product:

https://www.fregat.com.ua/en/wheels and rollers/wheel/50 24 160 shf-id1504

For high loads

For window productions

For warehouse and loading equipment

Specification:

Wheel outside diameter: 160 mm

Full height of the product: 190 mm

Full height of the product: 53 mm

Rolling Surface Material: polyurethane

Rim material: aluminum

Bracket Steel Thickness: 4,5 mm

The thickness of the steel of

mounting plate:

6 mm

Outside size of mounting plate: 140×110

The distance between the

mounting holes and their

diameter:

105x080x11

Hardness: 92 Shore A

Working temperature: $-20^{\circ}\text{C} - +80^{\circ}\text{C}$

Maximum load: 500 kg **Manufacturer:** Fregat

Description:

The rim of the wheel is made of cast aluminum, which forms an inseparable connection with the rolling surface through a chemical and geometric force. The polyurethane rolling surface has both high payload capacity and good elasticity, durability and low rolling resistance.