FREGAT LLC





49000, Dnipropetrovsk region, Dnipro city, Grushevsky Mikhail, 12, office 2-B Showroom and address for correspondence: пр. Александра Поля, дом 59, г. Днепр, Украина, 49101

> E-Mail: info@fregat.com.ua https://www.fregat.com.ua/ Tel/fax +380562362947



THE SERIES 50 POLYURETHANE / ALUMINIUM

Yellow polyurethane wheel with aluminum rim and ball bearings.

double swivel castor with brake 50 35x2 200 ШФ

Item code: 50 35x2 200 ШФ

Link to the product:

https://www.fregat.com.ua/en/wheels and rollers/wheel/50 35x2 200 shf-id1523

For high loads For window productions For warehouse and loading equipment

Specification:

Wheel outside diameter: 200 mm

250 mm Full height of the product:

45 mm Full height of the product:

Rolling Surface Material: polyurethane

Rim material: aluminum

Bracket Steel Thickness: 8 mm

The thickness of the steel of 8 mm

mounting plate:

Outside size of mounting plate: 135x110

The distance between the mounting holes and their

diameter:

105x80x12

92 Shore A Hardness:

-20°C — +80°C Working temperature:

Maximum load: 1000 kg Manufacturer: Fregat

Description:

The rim of the wheel is made of cast aluminum, which forms an inseparable connection with the rolling surface through a chemical and geometric force. The polyurethane rolling surface has both high payload capacity and good elasticity, durability and low rolling resistance.