

**THE SERIES 50 POLYURETHANE / ALUMINIUM**

Yellow polyurethane wheel with aluminum rim and ball bearings.

**swivel castor with brake and top plate 50 32 125 ШФ**

**Item code:** 50 32 125 ШФ

**Link to the product:**

[https://www.fregat.com.ua/en/wheels\\_and\\_rollers/wheel/50\\_32\\_125\\_shf-id1580](https://www.fregat.com.ua/en/wheels_and_rollers/wheel/50_32_125_shf-id1580)

For high loads

For window productions

For warehouse and loading equipment

**Specification:**

<b>Wheel outside diameter:</b>	125 mm
<b>Full height of the product:</b>	155 mm
<b>Full height of the product:</b>	40 mm
<b>Bracket Steel Thickness:</b>	3,5 mm
<b>The thickness of the steel of mounting plate:</b>	4 mm
<b>Outside size of mounting plate:</b>	105x80
<b>The distance between the mounting holes and their diameter:</b>	080x060x9
<b>Hardness:</b>	92 Shore A
<b>Working temperature:</b>	-20°C — +80°C
<b>Maximum load:</b>	350 kg
<b>Net weight:</b>	1,96 kg
<b>Manufacturer:</b>	Fregat

**Description:**

The rim of the wheel is made of cast aluminum, which forms an inseparable connection with the rolling surface through a chemical and geometric force. The polyurethane rolling surface has both high payload capacity and good elasticity, durability and low rolling resistance.