FREGAT LLC





49000, Dnipropetrovsk region, Dnipro city, Grushevsky Mikhail, 12, office 2-B Showroom and address for correspondence:

пр. Александра Поля, дом 59, г. Днепр, Украина, 49101

E-Mail: info@fregat.com.ua https://www.fregat.com.ua/ Tel/fax +380562362947



THE SERIES 29 ELASTIC RUBBER / POLYPROPYLENE

Elastic blue rubber wheel.

fixed castors 29 10 160 PT

Item code: 29 10 160 PT

Link to the product:

https://www.fregat.com.ua/en/wheels and rollers/wheel/29 10 160 rt-id202

For poor quality asphalt and pavement, outdoor uses For music and stage equipment

Specification:

Wheel outside diameter: 160 mm

Full height of the product: 190 mm

Full height of the product: - mm

Bracket Steel Thickness: 3 mm

The thickness of the steel of

mounting plate:

4 mm

Outside size of mounting plate: 135x114

The distance between the mounting holes and their

diameter:

105x080x11

Hardness: 65 Shore A

Working temperature: $-20^{\circ}\text{C} - +70^{\circ}\text{C}$

Maximum load: 300 kg

Net weight: 1,747 kg

Manufacturer: Torwegge

Description:

Rubber is connected to the rim of the wheel with volcanization process, low rolling resistance. The rim of the wheel: made by the method of casting under pressure from polypropylene, on a roller bearing, the color is black.