





49000, Dnipropetrovsk region, Dnipro city, Grushevsky Mikhail, 12, office 2-B Showroom and address for correspondence:

пр. Александра Поля, дом 59, г. Днепр, Украина, 49101

E-Mail: info@fregat.com.ua https://www.fregat.com.ua/ Tel/fax +380562362947



THE SERIES 29 ELASTIC RUBBER / POLYPROPYLENE

Elastic blue rubber wheel.

swivel castor with central hole 29 80 200 PT

Item code: 29 80 200 PT

Link to the product:

https://www.fregat.com.ua/en/wheels and rollers/wheel/29 80 200 rt-id208

For poor quality asphalt and pavement, outdoor uses For music and stage equipment

Specification:

Wheel outside diameter: 200 mm

Full height of the product: 235 mm

Full height of the product: 54 mm

Bracket Steel Thickness: 3 mm

Steel thickness of the upper

rotary panel:

4 mm

Outside size of mounting plate:

Diameter of central mounting 16.5

hole:

65 Shore A **Hardness:**

-20°C — +70°C Working temperature:

Maximum load: 300 kg

Net weight: 2,484 kg

Manufacturer: Torwegge

Description:

Rubber is connected to the rim of the wheel with volcanization process, low rolling resistance. The rim of the wheel: made by the method of casting under pressure from polypropylene, on a roller bearing, the color is black.