





49000, Dnipropetrovsk region, Dnipro city, Grushevsky Mikhail, 12, office 2-B Showroom and address for correspondence: пр. Александра Поля, дом 59, г. Днепр, Украина, 49101 E-Mail: info@fregat.com.ua

https://www.fregat.com.ua/



## THE SERIES 50 POLYURETHANE / ALUMINIUM

Yellow polyurethane wheel with aluminum rim and ball bearings.

swivel castor with top plate 50 20 150 ШИ

Item code: 50 20 150 ШИ

Link to the product:

https://www.fregat.com.ua/en/wheels and rollers/wheel/50 20 150 shi-id431

For high loads

For window productions

For warehouse and loading equipment

## **Specification:**

Wheel outside diameter: 150 mm

Full height of the product: 188 mm

Full height of the product: 52 mm

**Bracket Steel Thickness:** 3 mm

The thickness of the steel of

mounting plate:

4 mm

**Outside size of mounting plate:** 135x110

The distance between the

mounting holes and their

diameter:

105x080x11

**Hardness:** 92 Shore A

Working temperature:  $-20^{\circ}\text{C} - +80^{\circ}\text{C}$ 

Maximum load: 300 kg

Net weight: 2,18 kg

Manufacturer: RoCarr

## **Description:**

The rim of the wheel is made of cast aluminum, which forms an inseparable connection with the rolling surface through a chemical and geometric force. The polyurethane rolling surface has both high payload capacity and good elasticity, durability and low rolling resistance.