FREGAT LLC





49000, Dnipropetrovsk region, Dnipro city, Grushevsky Mikhail, 12, office 2-B Showroom and address for correspondence: пр. Александра Поля, дом 59, г. Днепр, Украина, 49101 E-Mail: info@fregat.com.ua

https://www.fregat.com.ua/



THE SERIES 50 POLYURETHANE / ALUMINIUM

Yellow polyurethane wheel with aluminum rim and ball bearings.

swivel castor with brake and top plate 50 30 100 ШИ

Item code: 50 30 100 ШИ

Link to the product:

https://www.fregat.com.ua/en/wheels and rollers/wheel/50 30 100 shi-id444

For high loads

For window productions

For warehouse and loading equipment

Specification:

Wheel outside diameter: 100 mm

Full height of the product: 125 mm

Full height of the product: 36 mm

Bracket Steel Thickness: 2 mm

The thickness of the steel of

mounting plate:

3 mm

Outside size of mounting plate: 105x80

The distance between the

mounting holes and their

diameter:

080x060x9

Hardness: 92 Shore A

Working temperature: $-20^{\circ}\text{C} - +80^{\circ}\text{C}$

Maximum load: 180 kg

Net weight: 0,94 kg

Manufacturer: RoCarr

Description:

The rim of the wheel is made of cast aluminum, which forms an inseparable connection with the rolling surface through a chemical and geometric force. The polyurethane rolling surface has both high payload capacity and good elasticity, durability and low rolling resistance.