FREGAT LLC





49000, Dnipropetrovsk region, Dnipro city, Grushevsky Mikhail, 12, office 2-B Showroom and address for correspondence: пр. Александра Поля, дом 59, г. Днепр, Украина, 49101 E-Mail: info@fregat.com.ua

https://www.fregat.com.ua/



THE SERIES 51 POLYURETHANE / CAST IRON

Yellow polyurethane wheel with cast iron rim and ball bearings.

swivel castor with top plate 51 24 200 ШТ-1

Item code: 51 24 200 ШТ-1

Link to the product:

https://www.fregat.com.ua/en/wheels and rollers/wheel/51 24 200 sht-1-id499

For high loads

For window productions

Specification:

Wheel outside diameter: 200 mm

Full height of the product: 264 mm

Full height of the product: 45 mm

Bracket Steel Thickness: 4.5 mm

The thickness of the steel of

mounting plate:

6 mm

Outside size of mounting plate: 175x140

The distance between the

mounting holes and their

diameter:

140x105x15

Hardness: 95 Shore A

Working temperature: $-20^{\circ}\text{C} - +80^{\circ}\text{C}$

Maximum load: 1200 kg

Net weight: 3,80 kg

Manufacturer: Torwegge

Description:

The rim of the wheel is made of cast iron, which forms an inseparable connection with the rolling surface through a chemical and geometric force. The polyurethane rolling surface has both high payload capacity and good elasticity, durability and low rolling resistance.