FREGAT LLC





49000, Dnipropetrovsk region, Dnipro city, Grushevsky Mikhail, 12, office 2-B Showroom and address for correspondence: пр. Александра Поля, дом 59, г. Днепр, Украина, 49101

E-Mail: info@fregat.com.ua https://www.fregat.com.ua/ Tel/fax +380562362947



THE SERIES 51 POLYURETHANE / CAST IRON

Yellow polyurethane wheel with cast iron rim and ball bearings.

fixed castors 51 14 300 ШТ

Item code: 51 14 300 ШТ

Link to the product:

https://www.fregat.com.ua/en/wheels and rollers/wheel/51 14 300 sht-id524

For high loads

For window productions

Specification:

Wheel outside diameter: 300 mm

Full height of the product: 355 mm

Full height of the product: - mm

Bracket Steel Thickness: 6 mm

The thickness of the steel of

mounting plate:

7 mm

Outside size of mounting plate: 200x160

The distance between the mounting holes and their

diameter:

160x120x15

Hardness: 95 Shore A

Working temperature: $-20^{\circ}\text{C} - +80^{\circ}\text{C}$

Maximum load: 1800 kg
Net weight: 6,98 kg

Manufacturer: Torwegge

Description:

The rim of the wheel is made of cast iron, which forms an inseparable connection with the rolling surface through a chemical and geometric force. The polyurethane rolling surface has both high payload capacity and good elasticity, durability and low rolling resistance.