FREGAT LLC





49000, Dnipropetrovsk region, Dnipro city, Grushevsky Mikhail, 12, office 2-B Showroom and address for correspondence: пр. Александра Поля, дом 59, г. Днепр, Украина, 49101 E-Mail: info@fregat.com.ua

https://www.fregat.com.ua/



THE SERIES 40 BLUE POLYURETHANE / NYLON (PROFI SERIES)

Blue polyurethane wheel with solid nylon rim and ball bearings.

double swivel castor with brake 40 35x2 200 WT

Item code: 40 35х2 200 ШТ

Link to the product:

https://www.fregat.com.ua/en/wheels and rollers/wheel/40 35x2 200 sht-id849

For high loads
For window productions
For furniture productions

Specification:

Wheel outside diameter: 200 mm

Full height of the product: 250 mm

Full height of the product: 45 mm

Rolling Surface Material: polyurethane

Rim material: nylon

Bracket Steel Thickness: 8 mm

The thickness of the steel of

mounting plate:

8 mm

Outside size of mounting plate: 135x110

The distance between the mounting holes and their

diameter:

105x80x12

Hardness: 93 Shore A

Working temperature: $-20^{\circ}\text{C} - +80^{\circ}\text{C}$

Maximum load: 1000 kg

Manufacturer: Torwegge

Description:

The rim of the wheel is made of white nylon, which forms an inseparable connection with the rolling surface through a chemical and geometric force. The polyurethane rolling surface has both high payload capacity and good elasticity, durability and low rolling resistance.