## FREGAT LLC





49000, Dnipropetrovsk region, Dnipro city, Grushevsky Mikhail, 12, office 2-B Showroom and address for correspondence:

пр. Александра Поля, дом 59, г. Днепр, Украина, 49101

E-Mail: info@fregat.com.ua https://www.fregat.com.ua/ Tel/fax +380562362947



## THE SERIES 50 POLYURETHANE / ALUMINIUM

Yellow polyurethane wheel with aluminum rim and ball bearings.

double swivel castor 50 26x2 160 ШТ

Item code: 50 26x2 160 ШТ

Link to the product:

https://www.fregat.com.ua/en/wheels and rollers/wheel/50 26x2 160 sht-id872

For high loads

For window productions

For warehouse and loading equipment

## **Specification:**

Wheel outside diameter: 160 mm

215 mm Full height of the product:

45 mm Full height of the product:

**Rolling Surface Material:** polyurethane

Rim material: aluminum

**Bracket Steel Thickness:** 8 mm

The thickness of the steel of 8 mm

mounting plate:

**Outside size of mounting plate:** 175x140

The distance between the mounting holes and their

diameter:

140x105x13

92 Shore A Hardness:

-20°C — +80°C Working temperature:

**Maximum load:** 1100 kg

Manufacturer: Torwegge

## **Description:**

The rim of the wheel is made of cast aluminum, which forms an inseparable connection with the rolling surface through a chemical and geometric force. The polyurethane rolling surface has both high payload capacity and good elasticity, durability and low rolling resistance.