FREGAT LLC





49000, Dnipropetrovsk region, Dnipro city, Grushevsky Mikhail, 12, office 2-B Showroom and address for correspondence: пр. Александра Поля, дом 59, г. Днепр, Украина, 49101 E-Mail: info@fregat.com.ua

https://www.fregat.com.ua/



THE SERIES 47 CAST POLYURETHANE / NYLON (PROFI SERIES)

A new generation of polyurethane wheels.

swivel castor with brake and top plate 47 30 200 ШИ

Item code: 47 30 200 ШИ

Link to the product:

https://www.fregat.com.ua/en/wheels and rollers/wheel/47 30 200 shi-id901

For high loads
For window productions
For warehouse and loading equipment

Specification:

Wheel outside diameter: 200 mm

Full height of the product: 235 mm

Full height of the product: 54 mm

Rolling Surface Material: cast PU

Rim material: nylon

Bracket Steel Thickness: 3 mm

The thickness of the steel of

mounting plate:

4 mm

Outside size of mounting plate: 135x110

The distance between the mounting holes and their

diameter:

105x080x11

Hardness: 90 Shore A

Working temperature: $-20^{\circ}\text{C} - +80^{\circ}\text{C}$

Maximum load: 300 kg

Net weight: 3,74 kg

Manufacturer: RoCarr

Description:

The wheel consists of cast soft polyurethane rolling surface, and a reinforced base of the wheel, made of solid nylon, formed through a chemical, force and geometric closure of rim and rolling surface. The polyurethane contact layer has both high load capacity and good elasticity, durability and low rolling resistance.