





49000, Dnipropetrovsk region, Dnipro city, Grushevsky Mikhail, 12, office 2-B Showroom and address for correspondence: пр. Александра Поля, дом 59, г. Днепр, Украина, 49101 E-Mail: info@fregat.com.ua

https://www.fregat.com.ua/ Tel/fax +380562362947



THE SERIES 12 STANDARD RUBBER / POLYPROPYLENE

Standard black rubber wheel.

swivel castor with top plate 12 20 200 PT

Item code: 12 20 200 PT

Link to the product:

https://www.fregat.com.ua/en/wheels and rollers/wheel/12 20 200 rt-id95

For garbage containers and scaffolding

Specification:

Wheel outside diameter: 200 mm

Full height of the product: 235 mm

Full height of the product: 54 mm

Bracket Steel Thickness: 3 mm

The thickness of the steel of

mounting plate:

4 mm

Outside size of mounting plate: 135x110

The distance between the mounting holes and their

diameter:

105x080x11

Hardness: 80-85 Shore A

Working temperature: $-20^{\circ}\text{C} - +60^{\circ}\text{C}$

Maximum load: 205 kg

Net weight: 2,898 kg

Manufacturer: Torwegge

Description:

The rim is made of polypropylene casting, roller bearing.